

exena.

XR90_PLAZA S3 SRC



DESCRIPTION	NORM EN ISO 20345:2011	RESULT	REQUIREMENT
UPPER: Microfiber with anti-abrasion film	5.4.3 Tear strength	270 N	≥ 60 N
	5.4.6 Water vapor permeability Coefficient	1,1 mg/cm ² h 15,6 mg/cm ²	≥ 0,8 mg/cm ² h ≥ 15,0 mg/cm ²
VAMP LINING: Breathable, abrasion resistance.	5.5.2 Tear strength	26 N	≥ 15 N
	5.5.3 Abrasion resistance (Wet)	No holes	25.600 cycles
	Abrasion resistance (Dry)	No holes	51.200 cycles
QUARTER LINING: Breathable, abrasion resistance.	5.5.2 Tear strength	26 N	≥ 15 N
	5.5.3 Abrasion resistance (Wet)	No holes	25.600 cycles
	Abrasion resistance (Dry)	No holes	51.200 cycles ≥
COUNTER LINING: Breathable, abrasion resistance.	5.5.2 Tear strength	26 N	≥ 15 N
	5.5.3 Abrasion resistance (Wet)	No holes	25.600 cycles
	Abrasion resistance (Dry)	No holes	51.200 cycles
SAFETY TOE CAP: Aluminum	5.3.2.6 Impact resistance	14 mm	≥ 14 mm
	5.3.2.7 Compression resistance	14 mm	≥ 14 mm
PIERCE-RESISTANCE: Textile pierce proof footbed.	6.2.1.1.3 Resistance to perforation	PASS	≥ 1100 N

EXENA SRL
via Breda 20
62012 Civitanova M. MC
ITALY

REA MC144207
Reg. Impr. Trib. MC 01336080435
C.F. e P. IVA 01336080435
Cap. Soc. € 25.823,00 i.v.

+39 0733 89 72 56
info@exena.com
amministrazione@pec.exena.it

exena.com

exena.

FOOTBED: Removable, cushioned, antistatic insole.	5.7.4.2 Abrasion resistance (Dry)	No holes	25.600 cycles
	Abrasion resistance (Wet)	No holes	12.800 cycles

OUTSOLE: PU , Antislip sole, SRC	5.8.3 Tear strength	7,4 kN/m	≥ 8 kN/m
	5.8.4 Abrasion resistance	178 mm ³	≤ 250 mm ³
	5.8.5 Flexing resistance	2,0 mm	≤ 4,0 mm
	6.4.2 Oils resistance	4 %	≤ 12%
	5.3.5.2 Determination of slip resistance on pressed ceramic tile floor with detergent solution.		
	Condition B (forward flat slip)	0,47	≥ 0,32
	Condition A (forward heel slip)	0,45	≥ 0,28
	5.3.5.3 Determination of slip resistance on stainless steel plate		
	Condition C (forward flat slip)	0,22	≥ 0,18
	Condition D (forward heel slip)	0,18	≥ 0,13

SIZES: 38-48

WEIGHT: (g)

38	39	40	41	42	43	44	45	46	47	48
886	914	942	970	998	1026	1054	1082	1110	1138	1166